SAYERLACK®
INNOVATIVE WOOD SOLUTIONS

COMPANY WITH
MANAGEMENT SYSTEM
- UNI EN ISO 9001 -
- UNI EN ISO 14001 -

Sherwin-Williams Italy S.r.l. – con unico socio
Via del Fiffo, 12 - 40065 Pianoro (BO) - Italia - C.P. 18
tel. +39 051 770 511 - fax +39 051 777 437
www.sayerlack.com
Cod. Fisc. e Reg. Impr. Bo 08866930152
P. IVA: IT 00494251200 - R.E.A. n. 313180
Cap. Soc. Euro 2.626.182 I.V. - Codice Mecc. Bo 014531

Company under the direction and coordination of The Sherwin-Williams Company, USA

Technical **Data Sheet**

DT0452/00
GENERAL PURPOSE POLYURETHANE THINNER

Supersedes previous issue dated 10/16/00 *DATE 11/03/04*

Technical characteristics:

Specific gravity (kg/l):	0.850 ± 0.030

General characteristics

Flash point:	-5°C
Drying speed (max 100 – min 0):	75
Shelf-life:	If the product is properly stored, shelf-life is unlimited.

DT0452/00 is suitable for polyurethane coatings.

DT0452/00 is manufactured with top quality raw materials and its excellent balance of components ensures a regular evaporation curve. Its evaporation speed is quite fast, reducing viscosity of polyurethane coatings, and increasing at the same time their pot-life.

DT0452/00 can dilute both polyurethane basecoats and topcoats in all seasons of the year except the hottest months when DT0040/00 is to be preferred.

N.B.: DATA PROVIDED ON THIS TECHNICAL DATA SHEET CORRESPOND TO OUR BEST KNOWLEDGE AND EXPERIENCE. WE ASSURE CONSISTENCY ON THE CHEMICAL-PHYSICAL CHARACTERISTICS OF OUR PRODUCTS, WITHIN THE TOLERANCE LIMITS SPECIFIED ON OUR TECHNICAL DATA SHEETS. RESPONSIBILITY OF FINAL RESULT OF PRODUCT APPLICATION IS FULLY UP TO THE USERS, WHO SHALL MAKE SURE THAT THE PRODUCT CORRESPONDS TO THEIR OWN NEEDS WITH REGARD TO APPLICATION SYSTEM, TO SUBSTRATES USED AS WELL AS TO WORKING CONDITIONS.
WARNING: ACTUAL VISCOSITY OF SOME PIGMENTED AND/OR THIXOTROPIC PRODUCTS MAY DIFFER FROM THE VISCOSITY SHOWN ON THE TECHNICAL DATA SHEET. DIFFERENCES ARE TO BE REGARDED AS ACCEPTABLE IF WITHIN 30% MAXIMUM.